

With or without
buzzerr

Multicolour
(3 or 7 colours)

Now also available
with UL approval

IP 65 / IP 69k



LED Installation beacon MC55 with UL approval

The compact LED installation beacon 240 Multicolour from WERMA is now also available with UL approval required for the USA as well as the high protection rating IP69k. This continues the success story of this small, attention-grabbing product and enables it to be used under extreme conditions around the world.

WERMA Signaltechnik GmbH + Co. KG
Dürbheimer Str. 15
D-78604 Rietheim-Weilheim
Phone +49 74 24 9557-0
Fax +49 74 24 9557-44
www.werma.com
info@werma.com

WERMA Italia S.r.l.
Via dell'Artigianato 42
29122 Piacenza
Italia
Phone +39 523 044 544
www.werma.it
info@werma.it

WERMA BENELUX
Poortakkerstraat 41C
9051 Sint-Denijs-Westrem
Belgium
Phone +32 9 220 31 11
www.wermabenelux.com
info@wermabenelux.com

WERMA USA Inc.
1266 Oakbrook Drive, Suite A
Norcross, GA 30093 USA
Phone +1 470 361 0600
www.werma.com
us-info@werma.com

WERMA Signaltechnik
Niederlassung Neuhausen am Rhf.
Rheingoldstrasse 50
8212 Neuhausen am Rheinfall
Switzerland
Phone +41 52 674 0060
Fax +41 52 674 0066
www.werma.ch
info@werma.ch

WERMA SARL
56, Rue Colière
69780 Mions
France
Phone +33 4 72 22 37 37
www.werma.fr
info@werma.fr



WERMA (UK) Ltd.
11 Regent Park
37 Booth Drive
Park Farm Industrial Estate
Wellingborough NN8 6GR
Great Britain
Phone +44 1536 486930
Fax +44 1536 514810
www.werma.co.uk
uksales@werma.co.uk

WERMA (Shanghai) Co., Ltd.
Building 8, No. 85, Mingnan Road,
Songjiang, Shanghai, P. R. C
201613
China
Phone +86 21 57 74-0022
Fax +86 21 57 74-6601
www.werma.com.cn
info@werma.com.cn

240 LED Multicolour Beacon MC55



Technical Specifications	
Dimensions (Ø x H)	55 mm x 46 mm (Protrusion from panel)
Housing	PC/ABS-Blend, black PC, black (UL approval)
Lens	PC, transparent
Fixing	Installation mounting M30
Colour options	Red, yellow, green, white, blue, violet, turquoise (RGB) Red, yellow, green (RGY)
Light effect	Permanent or Blinking light (1 Hz frequency)
Tone types and frequency	Pulse tone, 3400 Hz
Life duration light	Up to 50,000 h
Life duration buzzer	Up to 5,000 h



NEW



NEW

With buzzer				
Protection rating	IP 65			
Sound output	85 dB (A)			
	Voltage	Current consumption	Plug M12	Cable
Tricolor (RGY)	24 V DC	45 mA	240 220 55	240 210 55
Multicolour (RGB)	10-30 V DC	60 mA	240 120 50	240 110 50

UL approval with buzzer			
Protection rating	IP 69k		
	Voltage	Current consumption	Plug M12
Tricolor (RGY)	24 V DC	65 mA	240 440 55
Multicolour (RGB)	10-30 V DC	130 mA	240 340 50

Without buzzer				
Protection rating	IP 65			
	Voltage	Current consumption	Plug M12	Cable
Tricolor (RGY)	24 V DC	45 mA	240 240 55	240 230 55
Multicolour (RGB)	10-30 V DC	80 mA	240 140 50	240 130 50

UL approval without buzzer			
Protection rating	IP 69k		
	Voltage	Current consumption	Plug M12
Tricolor (RGY)	24 V DC	40 mA	240 420 55
Multicolour (RGB)	10-30 V DC	120 mA	240 320 50