

S1UK 24VACDC 120/240VAC UM 1VAC/DC

838000



Voltage monitoring relay, to monitor min. and max. voltage values, 0.40 - 400 Hz, measuring voltage 1 V AC/DC, width = 22.5 mm, UB = 24 V AC/DC, 120/240 V AC.

Technical details

General data	
Approval:	CE, UKCA, cULus Listed
Technical data	
Electrical data	
Supply voltage (V):	240 - 240 V
Type of supply voltage U1:	AC
Power consumption AC:	2 VA
Supply voltage 2 (V):	120 - 120 V
Type of supply voltage U2:	AC
Max. device circuit breaker:	Max. conductor cross section
Relay outputs	
Utilisation cat. AC/DC1 stand.:	EN 60947-4-1
Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Safety contacts: AC at UL:	240 VAC
Relay contact material:	AgCdO
Addit. contact details relay:	+ 3.0 µm Au
Environmental data	
Climatic suitability to ...:	EN 60068-2-78
Ambient temperature:	-10 - 55 °C
Condensation permitted?:	Not permitted

EMC to standard ...:	EN 60947-5-1, EN 61000-6-2
Vibration to standard ...:	EN 60068-2-6
Clearance & creepage dist. to:	EN 60947-1
Mechanical data	
Mounting position:	any
Housing material lower section:	PPO UL 94 V0
Housing material front plate:	ABS UL 94 V0
Housing material upper part:	PPO UL 94 V0
Connection terminal:	Screw terminal
Terminal style:	fixed
Flex. cond. c/s AWG info:	24 - 10 AWG
Height dimension:	87 mm
Width dimension:	22.5 mm
Depth dimension:	121 mm
Net weight:	150 g
Gross weight:	158 g
Environment	
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85364900
UNSPSC 25:	39122205
EAN-Code:	4046548007374
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371801
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000019
ETIM Reference Feature:	EC001438
Volume:	0.284 dm ³