

## PFU6 24V-240VAC/DC UM 0-690VAC/DC

841000



Fault voltage monitoring of welding transformers to VDE 0545, 6 measurement input circuits 0 - 690 V AC/DC, 50 Hz - 1 kHz, response voltage 24 V AC/DC, width 45 mm, UB = 24 - 42 V AC, 42 - 240 V DC.

### Technical details

#### General data

Approval: CE, UKCA

#### Technical data

#### Electrical data

Supply voltage (V): 24 - 240 V

Type of supply voltage U1: AC/DC

Power consumption AC: 4 VA

Power consumption DC: 2 W

#### Environmental data

Condensation permitted?: Not permitted

#### Mechanical data

Mounting position: any

Connection terminal: Screw terminal

Terminal style: fixed

Net weight: 240 g

Gross weight: 250 g

#### Environment

REACH compliance: contains min. 1 SVHC-substance

WEEE classification (08/2018): 5 devices (feed size < 50cm)

#### Commercial data

Harmonized System Code:	85364900
UNSPSC 25:	39122205
EAN-Code:	4046548007176
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371801
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000019
ETIM Reference Feature:	EC001438
Volume:	0.527 dm3