

S1WP 18A 110-230VAC/DC UM 0-415VAC 0%

890165



True power monitoring suitable for 1- and 3-phase supplies for frequency-controlled motors, 9 measuring ranges 0 - 1000 Hz, measuring voltage 0 - 415 V AC, 1 changeover contact, 1 analogue output 0 - 10 V DC or 4 - AC/20 mA, width = 22.5 mm, UB = 110 - 230 V AC/DC, measuring range from 0%.

Technical details

General data	
Approval:	CCC, CE, UKCA, cULus Listed
Technical data	
Electrical data	
Supply voltage (V):	230 - 230 V
Type of supply voltage U1:	AC
Power consumption AC:	5 VA
Max. device circuit breaker:	Max. conductor cross section
Measuring circuit	
U meas. range analogue input:	0 - 415 V
I meas. range analogue input:	18 - 18 A
Freq. meas. range analog i/p:	0 - 1000 Hz
Output signals during generator operation	
Uout during generator mode:	0 - -10 V
Relay outputs	
Utilisation cat. AC/DC1 stand.:	EN 60947-4-1
Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Safety contacts: AC at UL:	250 V AC
Relay contact material:	AgCdO
Addit. contact details relay:	+ 3.0 µm Au

Environmental data	
Climatic suitability to ...:	EN 60068-2-78
Ambient temperature:	0 - 55 °C
Condensation permitted?:	Not permitted
EMC to standard ...:	EN 61000-6-2, EN 61000-6-4
Vibration to standard ...:	EN 60068-2-6
Clearance & creepage dist. to:	EN 60947-1
Overvoltage category:	III
Pollution degree clear.&creep.:	2
Mechanical data	
Mounting position:	any
Housing material lower section:	PPO UL 94 V0
Housing material front plate:	ABS UL 94 V0
Housing material upper part:	PPO UL 94 V0
Connection terminal:	Screw terminal
Terminal style:	fixed
Flex. cond. c/s AWG info:	24 - 10 AWG
Height dimension:	87 mm
Width dimension:	22.5 mm
Depth dimension:	121 mm
Net weight:	140 g
Gross weight:	150 g
Environment	
REACH compliance:	contains min. 1 SVHC-substance
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	90303370
UNSPSC 25:	39122205
EAN-Code:	4046548055542

ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27210127
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002479
Volume:	0.294 dm ³